

Nom. Pipe Size	O	C <sup>2</sup>	Y <sup>2</sup>			Bolt Circle	No. and Size of Holes
			Weld Neck	Slip on Thrd.	Lap Joint		
<b>1.500 LB. FLANGES</b>							
1/2	120.7	22.2	60.3	31.7	31.7	82.5	4 - 22.2
3/4	130.2	25.4	69.8	34.9	34.9	88.9	4 - 22.2
1	149.2	28.6	73	41.3	41.3	101.6	4 - 25.4
1 1/4	158.7	28.6	73	41.3	41.3	111.1	4 - 25.4
1 1/2	177.8	31.8	82.5	44.4	44.4	123.8	4 - 28.6
2	215.9	38.1	101.6	57.1	57.1	165.1	8 - 25.4
2 1/2	244.5	41.3	104.8	63.5	63.5	190.5	8 - 28.6
3	266.7	47.6	117.5	73	73	203.2	8 - 31.7
3 1/2							
4	311.1	54	123.8	90.5	90.5	241.3	8 - 34.9
5	374.6	73	155.6	104.8	104.8	292.1	8 - 41.3
6	393.7	82.6	171.4	119.1	119.1	317.5	12 - 38.1
8	482.6	92.1	212.7	142.9	142.9	393.7	12 - 44.4
10	584.2	107.9	254	158.7	177.8	482.6	12 - 50.8
12	673.1	123.8	282.5	181	219.1	571.5	16 - 54
14	749.3	133.4	298.4		241.3	635	16 - 60.3
16	825.5	146.1	311.1		260.4	704,8	16 - 66.7
18	914.4	161.9	327		276.3	774,7	16 - 73
20	984.2	177.8	355.6		292.1	831,8	16 - 79.4
24	1168.4	203.2	406.4		330.2	990,6	16 - 92.1

NOTES:

1. Always specify bore when ordering.  
Includes 1/16" raised face in ISO1b. and 300 lb. standards.
2. Does not include 114" raised face in 400 lb. and heavier standards.
3. Other types, sizes and facings on application.

