

Nom. Pipe Size	O	C ²	Y ²			Bolt Circle	No. and Size of Holes
			Weld Neck	Slip on Thrd.	Lap Joint		
2500 LB. FLANGES							
1/2	133.4	30.2	73	39.7	39.7	88.9	4 - 22.2
3/4	139.7	31.7	79.4	42.9	42.9	95.2	4 - 22.2
1	158.8	34.9	88.9	47.6	47.6	108	4 - 25.4
1 1/4	184.2	38.1	95.2	52.4	52.4	130.2	4 - 28.6
1 1/2	203.2	44.4	111.1	60.3	60.3	146.1	4 - 31.7
2	235	50.8	127	69.8	69.8	171.5	8 - 22.2
2 1/2	266.7	57.1	142.9	79.4	79.4	196.9	8 - 31.7
3	304.8	66.7	168.3	92.1	92.1	228.6	8 - 34.9
3 1/2							
4	355.6	76.2	190.5	108	108	273.1	8 - 41.3
5	419.1	92.1	228.6	130.2	130.2	323.8	8 - 47.6
6	482.6	108	273.1	152.4	152.4	368.3	8 - 54
8	552.4	127	317.5	177.8	177.8	438.1	12 - 54
10	673.1	165.1	419.1	228.6	228.6	539.7	12 - 66.7
12	762	184.2	463.5	254	254	619.1	12 - 73

NOTES:

1. Always specify bore when ordering.
Includes 1/16" raised face in ISO1b. and 300 lb. standards.
2. Does not include 1/4" raised face in 400 lb. and heavier standards.
3. Other types, sizes and facings on application.

